



DURACLEAR'

Single-component, water-based clear finish

SHEEN	PRODUCT#	UPC	SIZE	CASE QTY
Satin	807100000	027426807105	1-Gallon	4
Semi-Gloss	807050000	027426807051	1-Gallon	4
Gloss	807000000	027426807006	1-Gallon	4

Sand and prepare floor according to NWFA-recommended methods. For preparation and application instructions, please see product data sheet.

Count on DuraClear to deliver excellent results from beginning to end.

A GREENGUARD-Certified, non-ambering, single-component, urethane floor finish that provides a consistent appearance every time. DuraClear offers excellent scratch, moisture and chemical resistance, and is perfect for residential and commercial interior hardwood floors.

- Formulated for use with Quick Coat stain as a complete system
- Single-component no mixing, no product waste
- Excellent scratch, moisture and chemical resistance
- Easy application with exceptional flow and leveling
- · Excellent coverage for better efficiency
- Two-hour recoat interval for faster return to service
- Non-ambering clear for a beautiful, finished appearance
- GREENGUARD Certified for low chemical indoor emissions
- · Complies with LEEDS criteria for low-emitting materials
- Easy soap-and-water cleanup

Get with the system.

DuraSeal® Quick Coat stain and water-based finishes are certified to GREENGUARD standards for low chemical emissions into indoor air.



SUPERIOR PROTECTION

2 HR.

TOPCOAT

To learn more, visit greenguard.org



Since 1898, generations of contractors have counted on us to deliver the highest quality wood floor coatings. You know DuraSeal Quick Coat stain as simply the best stain on the market.

And we know there is only one way to best protect your Quick Coat stain — by using premium DuraSeal water-based finishes.

Contact us today for a FREE product demo — visit duraseal-wb.com







PHYSICAL PROPERTIES			
Color	Clear		
Odor	Very low, mild amine		
Solids	29% to 33%		
Viscosity	90-155 centipoises		
Coverage	500 sq. ft./gallon		
Number of Coats	Two to three		
Leveling	Great		
Defoaming	Great		
VOC	125 Maximum		
Coefficient of Friction	≥ 0.5 (Passed)		
Dry Film Thickness	1.25 mil. coat		
Freeze/Thaw Stable	No		
Shelf Life	Two years		
Cleanup	Warm water		
Maintenance	DuraSeal Hardwood Floor Cleaner		
Storage	Room temperature		
Working Temperature	Ambient temp between 50 °F and 90 °F, humidity below 80%		
Applicator	Synthetic T-bar, roller or pad		
GREENGUARD Certified	Yes		
Comply with LEEDS criteria	Yes		
Dry Time (@ 77 °F and 50% relative humidity)			
Recoat	Two hours		
Foot Traffic	24 hours		
Return to Service	72 hours		
Full Cure	One week		
Furniture and Rugs	One week		
Gloss Level (@ 60)			
Satin	24 +/- 6		
Semi-Gloss	56 +/- 6		
Gloss	90 minimum		

