

QUICK COAT

2-Hour Penetrating Finish.

Simply the best stain/penetrating finish on the market.

Beautiful rich colors. Quick Coat's rich blend of oil and resin gives hardwood floors a bold, soft, satin sheen. With 31 packaged colors and 65+ intermix options your creativity for custom colors are endless.







QUICK COAT

2-Hour Penetrating Finish.

A UNIQUE FORMULA DESIGNED TO COLOR, SEAL AND PROVIDE EXCEP-TIONAL DURABILITY WITH A SURFACE THAT CAN BE TOPCOATED IN JUST 2-HOURS.

A GREENGUARD Certified, semi-transparent penetrating finish formulated to color, seal and provide exceptional durability when used on hardwood floors. Quick Coat is compatible with all DuraSeal water-based and oil-based finish systems. 31 packaged stains can be inter-mixed to provide endless custom color possibilities.

- Leading stain technology for the professional hardwood floor finisher
- 31 packaged colors providing endless intermix and custom color options
- · Formulated for easy application for professionals
- Excellent coverage for better efficiency
- 2-hour dry time to topcoat for a faster return to service



- Can be applied by rag, pad or buffing machine
- **GREENGUARD Certified for low chemical indoor emissions**

GET WITH THE SYSTEM.

DuraSeal Ouick Coat stain and Water-Based Finishes are certified to GREENGUARD standards for low chemical emissions into indoor air.



To learn more, visit greenguard.org



Since 1898, generations of contractors have counted on us to deliver the highest quality wood floor coatings. You know DuraSeal Quick Coat stain as simply the best stain on the market.

And we know there is only one way to best protect your Quick Coat stain—by using premium DuraSeal Water-Based Finishes.

Contact us today for a FREE product demo-visit duraseal-wb.com



duraseal.com • 1-800-364-1359 Please see website to download most recent product data sheet. ©2017 DuraSeal D-1199-0104-D







COLOR	ITEM # QUART	CASE QTY QUART	ITEM # GALLON	CASE QTY GALLON
112 Golden Oak	86112	12	81112	6
130 Early American	86130	12	81130	6
111 Provincial	86111	12	81111	6
124 Special Walnut	86124	12	81124	6
135 Cherry	86135	12	81135	6
145 Golden Pecan	86145	12	81145	6
140 Colonial Maple	86140	12	81140	6
141 Fruitwood	86141	12	81141	6
125 Red Mahogany	86125	12	81125	6
133 English Chestnut	86133	12	81133	6
102 Nutmeg	86102	12	81102	6
104 Chestnut	86104	12	81104	6
110 Neutral	86110	12	81110	6
137 Spice Brown	86137	12	81137	6
123 Coffee Brown	86123	12	81123	6
116 Antique Brown	86116	12	81116	6
128 Medium Brown	86128	12	81128	6
122 Mesquite	86122	12	81122	6
108 Royal Mahogany	86108	12	81108	6
121 Golden Brown	86121	12	81121	6
139 Rosewood	86139	12	81139	6
143 Sedona Red	86143	12	81143	6
131 Ebony	86131	12	81131	6
150 Gunstock	86150	12	81150	6
171 Dark Walnut	86171	12	81171	6
175 Jacobean	86175	12	81175	6
101 Country White	86101	4	81101	4
172 Classic Gray	86172	4	81172	4
170 Weathered Oak	86170	4	81170	4
173 Espresso	86173	12	81173	6
199 True Black	86199	12	81199	6

Sand and prepare floor according to NWFA recommended methods. For preparation and application instructions please see Product Data Sheet.

PHYSICAL PROPERTIES			
Solids	33% to 42%		
Viscosity	22-65 centipoises		
Coverage	500 sq. ft./gallon		
Number of Coats	1 to 2		
VOC	550		
Shelf Life	2 years		
Clean Up	Paint Thinner/Mineral Spirits		
Storage	Room temperature		
Working Temperature	Ambient Temp between 50°F and 90°F, humidity below 80%		
Applicator	Rag, Brush, Pad, Buffer		
GREENGUARD Certified	Yes		
Dry Time (@ 77°F and 50% relative humidity)	2 hours		