



DuraSeal[®]

DURACLEAR[®]

SEMI-GLOSS

All swatches have been water popped
and are shown in Warm Grey.

SATIN

GLOSS



FOR PROFESSIONAL USE ONLY

DURACLEAR®

Single-component water-based clear finish.

COUNT ON DURACLEAR TO DELIVER EXCELLENT RESULTS FROM BEGINNING TO END.

A GREENGUARD Certified, non-ambering, single-component, urethane floor finish that provides a consistent appearance every time. DuraClear offers excellent scratch, moisture and chemical resistance, and is perfect for residential and commercial interior hardwood floors.

- Formulated for use with Quick Coat stain as a complete system
- Single-component — no mixing, no product waste
- Excellent scratch, moisture and chemical resistance
- Easy application with exceptional flow and leveling
- Excellent coverage for better efficiency
- Two-hour recoat interval for faster return to service
- Non-ambering clear for a beautiful, finished appearance
- GREENGUARD Certified for low chemical indoor emissions
- Complies with LEEDS criteria for low-emitting materials
- Easy soap-and-water cleanup



GET WITH THE SYSTEM.

DuraSeal® Quick Coat stain and water-based finishes are certified to GREENGUARD standards for low chemical emissions into indoor air.

To learn more, visit greenguard.org



Since 1898, generations of contractors have counted on us to deliver the highest quality wood floor coatings. You know DuraSeal Quick Coat stain as simply the best stain on the market.

And we know there is only one way to best protect your Quick Coat stain — by using premium DuraSeal Water-Based Finishes.

Contact us today for a FREE product demo — visit duraseal-wb.com

@durasealwoodfinishes

SHEEN	PRODUCT #	UPC	SIZE	CASE QTY
Satin	807100000	027426807105	1-Gallon	4
Semi-Gloss	807050000	027426807051	1-Gallon	4
Gloss	807000000	027426807006	1-Gallon	4

Sand and prepare floor according to NWFA recommended methods. For preparation and application instructions, please see Product Data Sheet.

PHYSICAL PROPERTIES

Color	Clear
Odor	Very low, mild amine
Solids	29% to 33%
Viscosity	90-155 centipoises
Coverage	500 sq. ft./gallon
Number of Coats	Two to three
Leveling	Great
Defoaming	Great
VOC	125 Maximum
Coefficient of Friction	≥ 0.5 (Passed)
Dry Film Thickness	1.25 mil. coat
Freeze/Thaw Stable	No
Shelf Life	Two years
Clean Up	Warm water
Maintenance	DuraSeal Hardwood Floor Cleaner
Storage	Room temperature
Working Temperature	Ambient temp between 50 °F and 90 °F, humidity below 80%
Applicator	Synthetic t-bar, roller or pad
GREENGUARD Certified	Yes
Comply with LEEDS criteria	Yes
Dry Time (@ 77 °F and 50% relative humidity)	
Recoat	Two hours
Foot Traffic	24 hours
Return to Service	72 hours
Full Cure	One week
Furniture and Rugs	One week
Gloss Level (@ 60)	
Satin	24 +/- 6
Semi-Gloss	56 +/- 6
Gloss	90 minimum



Premium Wood Floor Finishes

duraseal.com • 800-364-1359
Please see website to download most recent product data sheet.
© DuraSeal DRSL847/18
009760001-99