

DuraSeal®

Premium Wood Finishes

ADD SPORTS FLOORS TO YOUR BUSINESS PLAN.

Our MFMA-approved products are ideal for finishing sports floors in athletic centers, schools and more.



SPORTS FLOORS ARE BIG BUSINESS.

Use our high-quality, MFMA-approved flooring products to get in the game.



APPLICATION METHOD	DRY TIME	COVERAGE	VOC	% SOLIDS	CLEANUP
Brush, Pad, T-bar, Lambswool	Dry to Touch: 30 min Recoat: 2 hrs	500 sq. ft. per gallon	525 g/L	39.50-41.50	Mineral Spirits or Paint Thinner

QT: 865604444/GAL: 81560000



APPLICATION METHOD	DRY TIME	COVERAGE	VOC	% SOLIDS	CLEANUP
Brush, Pad, T-bar, Roll	Recoat: 2 hrs	500-600 sq. ft. per gallon	275 g/L	29.7-32.7	Warm Water

GAL: 801110000



APPLICATION METHOD	DRY TIME	COVERAGE	VOC	% SOLIDS	CLEANUP	GLOSS LEVEL
Brush, Pad, T-bar, Roll	Recoat: 2 hrs Final Coat: 24 hrs	500-600 sq. ft. per gallon	100 g/L	29.0-33.0	Warm Water	>90

GAL: 806000000



APPLICATION METHOD	DRY TIME	COVERAGE	VOC	% SOLIDS	CLEANUP	GLOSS LEVEL
Brush, Pad, T-bar, Roll	2-3 hrs	500-600 sq. ft. per gallon	<275	29.5-32.5	Warm Water	>90

GAL: 994100000/5 GAL: 994500000



APPLICATION METHOD	DRY TIME	COVERAGE	VOC	% SOLIDS	CLEANUP	GLOSS LEVEL
Brush, Pad, T-bar, Lambswool, Roll	8 hrs minimum	500-600 sq. ft. per gallon	<550	44-47	Mineral Spirits	>90

QT: 334604444/GAL: 33410000/5 GAL: 33450000

All of these products meet or exceed the MFMA standards for coefficient of friction, gloss level and chemical resistance.



GET TO KNOW THE MFMA

THE SPORTS FLOORING AUTHORITY SINCE 1897

The MFMA sets the worldwide standard for athletic floor best practices through development of installation techniques, education and certification of high-quality sports flooring products.



Premium Wood Finishes