

DURACLEAR[™] MAX POLY

Two-component water-based clear finish.

More than a promise of great results.
The ultimate look & protection.

Ultimate ease. DuraClear Max gives you great looks without a lot of extra work. With its excellent flow and leveling, it's a breeze to apply. And with its longer pot life, there's less waste. DuraClear Max also offers superior coverage for better efficiency and faster return to service, which is good for both your customers and your bottom line.



FOR PROFESSIONAL USE ONLY



DURACLEAR™ MAX

Two-component water-based clear finish.

COUNT ON DURACLEAR™ MAX TO DELIVER THE ULTIMATE LOOK & PROTECTION.

A GREENGUARD Certified, non-ambering, two-component, urethane/acrylic floor finish specifically made for commercial and high traffic residential floors. DuraClear Max offers excellent scratch, moisture, chemical and slip resistance, which means it provides a level of durability you can stake your reputation on.

- Formulated for use with Quick Coat stain for a system guarantee
- High solids, high build formula offering the ultimate durability
- Two-component technology for maximum performance in scratch, moisture and chemical resistance
- Superior flow and leveling making it a breeze to apply
- 6-hour pot life allows for less product waste
- Excellent coverage for better efficiency
- 2-hour recoat interval for faster return to service
- Non-ambering clear for a beautiful finished appearance
- GREENGUARD Certified for low chemical indoor emissions
- Complies with LEEDS criteria for low emitting materials
- Easy soap and water clean up



GET WITH THE SYSTEM.

DuraSeal Quick Coat stain and Water-Based Finishes are certified to GREENGUARD standards for low chemical emissions into indoor air.

To learn more, visit greenguard.org



Since 1898, generations of contractors have counted on us to deliver the highest quality wood floor coatings. You know DuraSeal Quick Coat stain as simply the best stain on the market.

And we know there is only one way to best protect your Quick Coat stain—by using premium DuraSeal Water-Based Finishes.

Contact us today for a FREE product demo—visit duraseal-wb.com

  @durasealwoodfinishes

SHEEN	PRODUCT #	UPC	SIZE	CASE QTY
Satin	809100000	027426809109	1-Gallon	2
Semi-Gloss	809050000	027426809055	1-Gallon	2
Gloss	809000000	027426809000	1-Gallon	2

Sand and prepare floor according to NWFA recommended methods. For preparation and application instructions please see Product Data Sheet.

PHYSICAL PROPERTIES

Color	Clear
Odor	Very low, mild amine
Solids	33% to 36% Crosslinked
Viscosity	55-100 centipoises
Coverage	500-600 sq. ft./gallon
Number of Coats	2 to 3
Pot Life	6 hours
Leveling	Excellent
Defoaming	Excellent
VOC	275 Maximum Crosslinked
Coefficient of Friction	≥ 0.5 (Passed)
Dry Film Thickness	1.4 mil/coat
Freeze/Thaw stable	Yes
Shelf Life	2 years
Clean Up	Warm water
Maintenance	DuraSeal Hardwood Floor Cleaner
Storage	Room temperature
Working Temperature	Ambient Temp between 50°F and 90°F, humidity below 80%
Applicator	Synthetic T-bar, Roller or Pad
GREENGUARD Certified	Yes
Comply with LEEDS Criteria	Yes
Dry Time (at 77°F and 50% relative humidity)	
Recoat	2 hours
Foot Traffic	24 hours
Return to Service	72 hours
Full Cure	1 week
Furniture and Rugs	1 week
Gloss Level (at 60)	
Satin	17 +/- 5
Semi-Gloss	40 +/- 5
Gloss	90 minimum

DURASEAL®
Premium Wood Floor Finishes

duraseal.com • 1-800-364-1359
Please see website to download most recent product data sheet.
©2017 DuraSeal
D-1379-0112B