

# DuraSeal®

Premium Wood Finishes

## DURACLEAR® POLY

Single-component, water-based clear finish

**More than a beautiful floor.  
A delighted customer.**

The reliable choice. Use DuraClear when you want an amazing finish, clarity and even more protection. And because it's water based, DuraClear is VOC compliant, fast drying and does not leave a lasting odor.

Available in Gloss, Semi-Gloss, Satin and **NEW** Flat sheens.



**THIS FLOOR** RED OAK WITH QUICK COAT™ NEUTRAL + DURACLEAR SEMI-GLOSS



FOR PROFESSIONAL USE ONLY

## DURACLEAR®

Single component, water-based clear finish

### Count on DuraClear to deliver excellent results from beginning to end.

A GREENGUARD Certified, non-ambering, single-component urethane floor finish that provides a consistent appearance every time. DuraClear offers excellent scratch, moisture and chemical resistance, and is perfect for residential and commercial interior hardwood floors.

- Formulated for use with Quick Coat™ stain as a complete system
- Single component — no mixing, no product waste
- Excellent scratch, moisture and chemical resistance
- Easy application with exceptional flow and leveling
- Excellent coverage for better efficiency
- Two-hour recoat interval for faster return to service
- Non-ambering clear for a beautiful finished appearance
- GREENGUARD Certified for low chemical indoor emissions
- Complies with LEEDS criteria for low-emitting materials
- Easy soap-and-water cleanup



### Get with the system.

DuraSeal® Quick Coat stain and water-based finishes are certified to GREENGUARD standards for low chemical emissions into indoor air.

To learn more, visit [greenguard.org](http://greenguard.org)



Since 1898, generations of contractors have counted on us to deliver the highest quality wood floor coatings. You know DuraSeal Quick Coat stain as simply the best stain on the market.

And we know there is only one way to best protect your Quick Coat stain — by using premium DuraSeal water-based finishes.

Contact us today for a FREE product demo — visit [duraseal-wb.com](http://duraseal-wb.com)

@durasealwoodfinishes

SHEEN	PRODUCT #	UPC	SIZE	CASE QTY
<b>NEW</b> Flat	807110000	027426807112	1 Gallon	4
Satin	807100000	027426807105	1 Gallon	4
Semi-Gloss	807050000	027426807051	1 Gallon	4
Gloss	807000000	027426807006	1 Gallon	4

**Sand and prepare floor according to NFWA recommended methods. For preparation and application instructions, please see Product Data Sheet.**

### PHYSICAL PROPERTIES

Color	Clear
Odor	Very low, mild amine
Solids	29% to 33%
Viscosity	90-155 centipoises
Coverage	500 sq. ft./gallon
Number of Coats	Two to three
Leveling	Great
Defoaming	Great
VOC	125 Maximum
Coefficient of Friction	≥ 0.5 (Passed)
Dry Film Thickness	1.25 mil. coat
Freeze/Thaw Stable	No
Shelf Life	Two years
Cleanup	Warm water
Maintenance	DuraSeal Hardwood Floor Cleaner
Storage	Room temperature
Working Temperature	Ambient temp between 50 °F and 90 °F, humidity below 80%
Applicator	Synthetic t-bar, roller or pad
GREENGUARD Certified	Yes
Comply with LEEDS criteria	Yes
<b>Dry Time (@ 77 °F and 50% relative humidity)</b>	
Recoat	Two hours
Foot Traffic	24 hours
Return to Service	72 hours
Full Cure	One week
Furniture and Rugs	One week
<b>Gloss Level (@ 60)</b>	
Flat	<10 at 60 and 85
Satin	24 +/- 6
Semi-Gloss	56 +/- 6
Gloss	90 minimum



[duraseal.com](http://duraseal.com) • 800-364-1359  
Please see website to download most recent product data sheet.

© DuraSeal 03/23 DRSL 1092/22 D-1377-0112D

Premium Wood Finishes